

Hopper/Auger Feed System [Inventory ID #1379729]



Hopper/Auger Feed System

- MAIN COMPONENTS:
 - Approx. 5-Yard Live Bottom Feed Hopper
 - Hopper Dimensions:
 - 91 inches Wide
 - 52 inches Deep
 - 76 inches High
 - Comes with (5) 10ft Long Chain-Driven Feed Augers
 - 5in Diameter Flights with Varying Pitch
 - Main Drive: Hyundai/Bonfiglioli 3HP Electric Motor with Inline Gear Reducer
 - Input Speed: 1760 RPM
 - Voltage: 575 Volt
 - Ratio: 178-1
 - Hopper Mounted on Steel Wide Flange Base
 - Complete with Kistler-Morse Model SVS-2000 4 Load Cell Scale
 - Voltage: 115/230 Volts
 - 13in Dia. x 30ft Long Enclosed U-Shape Transfer Auger
 - 7in Diameter Main Shaft with 3in Flights
 - 13in Pitch
 - 10HP Drive Motor
 - Belt Driving a Dodge Size 4 Shaft Mount Reducer
 - Ratio: 39.107-1
 - Auger Speed: 22.5 RPM
 - Tertiary Discharge Auger with 1-Yard Material Holding Hopper

- 12in Dia. x 10ft Auger
 - 4in Shaft with 4in Flights
 - 12in Pitch
 - Trough Width: 15in
- 3HP Drive Motor
- Speed: 1160 RPM
- Voltage: 575 Volt
- Belt Driving a SM-Cyclo Reducer
 - Ratio: 165-1
 - Output Speed: 7.03 RPM
 - 1 – 1 Ratio Chain-Drive to Auger
- Hopper Comes with Dual Oli Bin Vibrators
 - Power Output: 0.15HP
 - Speed: 3600 RPM
 - Voltage: 115 VAC

- Location: Savona, British Columbia, Canada

View More [Augers](#)